



H₂O GL Series

Innovative. Efficient. Dependable. Dunkirk

Glass Lined Indirect Water Heater

- Easy to Install
- Low Pressure Drop
- Magnesium Anode Rod Corrosion Protection
- Enameled Coated Steel Tank and Coil
- Minimal Standby Losses
- Flexible Scratch Resistant Jacket
- Aquastat Sensor Well
- Temperature Pressure Relief Valve
- Residential Limited Warranty:
Tank, 8-Years; Parts, 5-Years
- Commercial Limited Warranty:
Tank, 5-Years; Parts, 2-Years



H2O Glass Lined Indirect Water Heater

Item Number	Storage Volume	Coil Heating Surface	Dimensions (Inches)		Piping Connections N.P.T.		Approx. Wgt.
	Gallons	Square Feet	Height	Diameter	Domestic Water In/Out	Boiler Water In/Out	(lbs.)
H2OIG30DK	31	6.35	33	24	1	1	119
H2OIG40DK	42	14	45	24	1	1	180
H2OIG50DK	53	14	51	24	1	1	200
H2OIG80DK	79	20.7	48	30	1	1	243
H2OIG105DK	106	26	62	30	1	1	393

Item Number	Max. First Hour Rating	Continuous Rating	Boiler Output Needed	Boiler Water Flow Through the Coil	Pressure Drop Through the Coil
	Gal./Hr. @	Gal./Hr. @	MBH	(Gal./Min.)	(Ft. Water)
	115° F	115° F			
H2OIG30DK	116	93	75	14.0	7.5
	155	124	100		
H2OIG40DK	198	162	105	14.0	10.7
	256	220	120		
H2OIG50DK	212	169	110	14.0	10.7
	310	268	140		
H2OIG80DK	228	164	110	14.0	15.9
	346	281	180		
H2OIG105DK	270	175	115	14.0	19.7
	440	345	220		

Note: All ratings are based on 180° F boiler water supply temperature. Domestic hot water 70° F rise, 45° F water inlet temperature. Specifications subject to change without notice.

Standard Equipment

Smooth enameled coil, magnesium anode rod and temperature pressure relief valve, Honeywell Aquastat. Water tank temperature gauge.



Honeywell Aquastat L4080B1352 (field installed)



ECR International, Inc. 2201 Dwyer Avenue, Utica, NY 13501
Tel. 800 253 7900
www.ecrinternational.com

All specifications subject to change without notice.
©2019 ECR International, Inc.
PN 240012393 Rev. B [02/07/19]