

Twin Pipe Vent Submittal & Specifications

Engineer:
Project Name:
•
Project Location:
•
Contractor:

SPECIFICATIONS:

Natalini polypropylene vent components are used on gas fired condensing boilers with a sustained maximum flue gas temperature of 230°F/110°C. The Twin Pipe assembly allows exhaust flue and intake flue to be separated from each other. Fresh air is drawn in at a different area from the flue terminal location. The polypropylene venting material has a wall thickness of 2mm. The piping is connected with Silicon O-Rings for an airtight seal. A factory supplied metal clamp must be used to secure single wall twin pipe polypropylene vent pieces to each other.

CERTIFICATION AND APPOVALS:

This venting has been tested in accordance with and is in compliance with the applicable requirements of ULC-S636 per UL reports 188786-2546036 and 188786-70036223.

INSTALLATION:

Installation shall conform to requirements of authority having jurisdiction or in absence of such requirements: USA - National Fuel Gas Code, ANSI Z223.1/NFPA 54, UL 1738; Canada - Natural Gas and Propane Installation Code, CAN/CSA B149.1, ULC S636

Twin Vent Piping from a single manufacturer must be used throughout the entire vent system, must be installed in accordance with the Installation and Operations manual supplied with the condensing boiler, and/or the instructions supplied with the vent piping.

- Proper application of the securing mechanism (metal clamp supplied with the venting) is necessary for any use of Twin Pipe Polypropylene venting on exhaust or air intake.
- The venting is connected by a push-fit gasket. If lubricant is needed use water to aid with the install of the vent piping.
- Straight lengths of piping can be cut per the installation instructions.



PN 615000482 REV. A [11/15/2020]



STRAIGHT LENGTHS OF TWIN VENT PIPE: LENGTH

Diameter 2" (60 mm)

Diameter 3" (80 mm)

Diameter 4" (110 mm)



Twin Pipe Elbows 45 & 90

Diameter 2" (60 mm)

Diameter 3" (80 mm)

Diameter 4" (110 mm)





Terminations Vertical & Horizontal

Diameter 2" (60 mm)

Diameter 3" (80 mm)

Diameter 4" (110 mm)





2201 Dwyer Avenue, Utica, NY 13501 Tel. 800 325 5479 www.ecrinternational.com All specifications subject to change without notice. ©2020 ECR International, Inc.