

Dunkirk® | EW II Series II

Innovative. Efficient. Dependable. Dunkirk.







Empire Water II

Up to 86.5% AFUE High Efficiency Oil Fired Hot Water Boiler

- Available in 8 sizes from 91 to 245 Mbh.
- Dependable Cast Iron Heat Exchanger with Cast Iron Push Nipples. The Sections and Push Nipples expand at the same rate when heated. By using similar materials instead of less expensive gaskets the boiler maintains a water tight seal over time.
- Honeywell High Limit and Circulator Relay Control.
 - Digital Temperature Display and Diagnostics.
- Less Coil: Control monitors water temperature and delays the burner starting until any residual heat has been transferred. Thermal purge logic measures rate of temperature change inside the boiler and delays burner firing accordingly. This maximizes efficiency by turning on the burner only when needed.
- With Coil: Low Limit Control seeks maximum temperature to satisfy domestic hot water call bypassing thermal purge logic.
- Atmospheric Chimney Vent Boiler.
- Optional Tankless Heater Coil.
- Textured paint Jacket.
- 20 Year Non-Prorated Warranty (Residential Applications).



Dunkirk EW II Series II Oil-Fired Hot Water Boiler

Dimensions/Weights				Model	No. of Sec.	Input		Heating Capacity (MBH) ^{(1) (2)}	Net AHRI Rating, Water (MBH) ^{(1) (5)}	Minimum Chimney Size/ Height	Tankless Coil GPM's	AFUE % ⁽²⁾
						G.P.H. ⁽³⁾	MBH ⁽¹⁾					
				3EW.65	3	0.65	91	80	70	8" x 8" x 15'	2.90	86.3%
				3EW.75	3	0.75	105	92	80	8" x 8" x 15'	3.00	85.2%
				3EW.100	3	1.00	140	120	104	8" x 8" x 15'	3.25	84.0%
				4EW.90	4	0.90	126	111	97	8" x 8" x 15'	3.15	86.0%
				4EW1.25	4	1.25	175	151	131	8" x 8" x 15'	3.50	85.0%
				4EW1.50	4	1.50	210	179	156	8" x 8" x 15'	3.75	84.0%
				*5EW1.20	5	1.20	168	147	128	8" x 8" x 15'	3.45	86.5%
				5EW1.75	5	1.75	245	210	183	8" x 8" x 15'	4.00	84.3%
*Per Energy Star specifications, AFUE is rounded to the nearest whole percentage point. As such, this product qualifies for Energy Star.												
(1) Mbh = 1,000 BTU per hour [BTU = British Thermal Unit]												
(2) Heating Capacity based on 13% CO ₂ with a 0.02" w.c. draft over fire, and a #1 smoke or less. Testing was done in accordance with the D.O.E. (Department of Energy) test procedure.												
(3) G.P.H. = Gallons per hour oil at 140,000 BTU per gallon												
(4) A.F.U.E. = Annual Fuel Utilization Efficiency based upon D.O.E. test procedure.												
(5) Net AHRI Water Ratings based on piping and pickup allowance of 1.15. Consult manufacturer before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.												
General Information (See Installation, Operation and Maintenance Manual for complete instructions)												
				Clearances ⁽⁶⁾ Required distances measured from boiler. ⁽⁷⁾ Service, proper operation clearance recommendation.		Combustible Materials (Required) ⁽⁶⁾	Servicing ⁽⁷⁾	Flue to Combustible Clearance				
					Top	6" (15.2 cm)	24" (61 cm)	9" (22.9 cm)				
					Left Side	6" (15.2 cm)	No Requirement					
					Right Side	24" (61 cm)	No Requirement					
					Base	Non-Combustible	No Requirement					
					Front	24" (61 cm)	No Requirement					
					Back	6" (15.2 cm)	No Requirement					
Connections		Return/Supply Water 1-1/4" NPT										
Electrical		120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended)										
Water Content		3EW - 9.6 Gallons, 4EW - 11.6 Gallons, 5EW - 13.7 Gallons										
Standard Equipment		Boiler Control Module: Boilers without Tankless Heater Coil - Honeywell Combination High Limit Control and Circulator Relay. Boilers with Tankless Heater Coil - Honeywell Combination High Limit and Circulator Relay and Low Limit Control. Heat Exchanger: Cast Iron Sections with Cast Iron Push Nipples and Swing Door. Combustion: Completely installed and wired Beckett AFG Series Oil Burner (3 & 4 Section F Head; 5 Section MD Head) equipped with Nozzle, Primary Control, CAD Cell, PSC Motor, Interrupted Duty Ignition and Clean Cut Pump; Flue Brush; Swing Fire Door with Insulation (Vacuum Formed Ceramic Fiber), Target Wall (Vacuum Formed Refractory Ceramic Fiber); Dura Blanket Insulation Chamber. Chamber, and Barometric Draft Control 6". Other: Assembled Cast Iron Boiler with Insulated Jacket, Combination Temperature/Pressure Gauge, Circulator Pump wired with 5' harness for supply or return mounting in the field, 3/4" Boiler Drain Valve, 30 psi ASME Relief Valve, extra Boiler Tap for Expansion Tank or Air Elimination.										
Options		Beckett or Riello Burner, Manual Reset High Limit with plug-in Molex connector.										
Models	Dimensions			Wgt. (lbs.)	Certifications	   						
	A	B	C									
3EW	14-1/2"	6"	8"									
4EW	17-3/4"	6"	9-5/8"									
5EW	21"	6"	11-1/2"									

All ratings and specifications subject to change.

PN 240009785 Rev. 12/14

Contractor Assistance: 800.325.5479



P.O. Box 4729
Utica, New York 13504
tel: 315.797.1310 • fax: 315.797.3762
www.dunkirk.com

